

Brilliant, Highly Visible Signage even in Open Spaces with Natural Lighting.



SF1H Series			
	TH-55SF1H	TH-49SF1H	TH-42SF1H
Screen Size	55-inch	49-inch	42-inch
LCD Panel	IPS / Edge LED		
Brightness	700 cd/m ²		
Contrast / Dynamic Contrast	1,300:1 / 50,000:1		

High Image Quality and Visibility

- High 700 cd/m² Brightness with IPS Panel for Excellent Off-Axis Visibility in Bright Environments
- The IPS Panel Has a Wide Viewing Angle and Minimal Color Fluctuations
- LED Backlit Panel Enables Bright and Detailed Picture Quality with Low Power Consumption
- Stylish Design with Narrow 6.3 mm (0.25") Bezel Maximizes Screen Display Area

Durability

- Robust Professional-Grade Panel Resists Image Lag and Burn-in
- Quick Failover and Failback Safeguards via Automatic Signal Detection and Input Switching Functions
- Designed for Stable Continuous 24/7 Operation

Practical and Cost-Effective

- DIGITAL LINK Single-Cable Connection Transmits Video, Audio, and Control Signals for Up to 150 m (492 ft)*
- Built-in USB Media Player Provides Video and Still-image Playback via USB
- Copy and Share Settings Information Between Displays Using USB Cloning Function for Improved Picture Consistency
- DVI-D and RS-232C Daisy-chain Connection Capability (Up to 10 Units)
- Includes 10 W + 10 W Built-in Speakers

* Requires CAT 5e STP cable or above.

Specifications

Model	TH-55SF1H	TH-49SF1H	TH-42SF1H
Display panel			
Screen size (diagonal)	55-inch (1,387 mm)	49-inch (1,232 mm)	42-inch (1,064 mm)
Panel type	IPS/Edge LED		
Aspect ratio	16:9		
Effective display area (W x H)	1,209 x 680 mm (47.6" x 26.7")	1,073 x 604 mm (42.2" x 23.7")	927 x 521 mm (36.5" x 20.5")
Number of pixels (H x V)	1920 x 1080		
Brightness*1	700 cd/m ²		
Contrast ratio	1,300:1		
Dynamic contrast	50,000:1		
Response time	8 ms (G to G)		
Viewing angle (Horizontal/vertical)	178 °/178 ° (CR ≥ 10)		
Connection terminal			
Video In	BNC x 1 (Shared with Component Video/RGB In)		
Audio In (L/R)	Stereo Mini-Jack (M3) x 1 (Shared with Component Video/RGB In)		
HDMI In	HDMI TYPE A connector x 2		
Component Video/RGB In	BNC x 1 set		
Audio In (L/R)	Stereo Mini-Jack (M3) x 1 (Shared with Video In)		
DVI-D In	DVI-D 24-pin x 1 (DVI Revision 1.0 compliant), HDCP 1.1 compatible		
Audio In (L/R)	Stereo Mini-Jack (M3) x 1 (Shared with PC In)		
PC In	Mini D-sub 15-pin (DDC2B compatible) x 1		
Audio In (L/R)	Stereo Mini-Jack (M3) x 1 (Shared with DVI-D In)		
DVI-D Out	DVI-D 24-pin x 1 (DVI Revision 1.0 compliant), HDCP 1.1 compatible		
Audio Out (L/R)	Stereo Mini-Jack (M3) x 1		
USB memory	USB TYPE A connector x 1, DC 5 V/1 A (USB 3.0 is not supported)		
Control			
Serial In/Out	D-sub 9-pin x 1/x 1, RS-232C Compatible		
LAN/DIGITAL LINK	RJ45 x 1, 100BASE-TX, compatible with PLink™		
IR In/Out	Stereo Mini-Jack (M3) x 1 / x 1		
Audio			
Built-in speaker	20 W [10 W + 10 W]		
Electrical			
Power requirements	110–127 V AC, 50/60 Hz, 220–240 V AC, 50/60 Hz		
Power consumption	190 W	175 W	155 W
On mode average power consumption*2	Approx. 145 W	Approx. 130 W	Approx. 110 W
Power off condition	Approx. 0.3 W		
Standby condition	Approx. 0.5 W		
Mechanical			
Dimensions (W x H x D)	1,229 x 699 x 72 mm (48.4" x 27.6" x 2.8")	1,093 x 623 x 72 mm (43.1" x 24.6" x 2.8")	947 x 541 x 72 mm (37.3" x 21.3" x 2.8")
Dimensions (W x H x D) (Excluding handle part)	1,229 x 699 x 57 mm (48.4" x 27.6" x 2.3")	1,093 x 623 x 57 mm (43.1" x 24.6" x 2.3")	947 x 541 x 57 mm (37.3" x 21.3" x 2.3")
Bezel width	T/R/L/B 6.3 mm (0.25")		
Weight	Approx. 24.9 kg (54.9 lbs)	Approx. 19.2 kg (42.4 lbs)	Approx. 15.5 kg (34.2 lbs)
Pitch for wall-hanging	VESA compliant 400 x 400 mm (15.8" x 15.8")		200 x 200 mm (7.9" x 7.9")
Installation orientation	Landscape/Portrait (Angle adjustment 0–45 degrees for both left and right)		
Installation angle	0–45 degrees forward/backward with landscape/portrait setting (Angle adjustment is not possible for forward/backward tilting installation.)		
Environment			
Operating environment	Temperature: 0 °C to 40 °C (32 °F to 104 °F) for up to 1,400 m altitude / 0 °C to 35 °C (32 °F to 95 °F) for between 1,400 m and 2,800 m altitude, Humidity: 20 % to 80 % (Non-condensation)		
Storage environment	Temperature: -20 °C to 60 °C (-4 °F to 140 °F) Humidity: 20 % to 80 % (Non-condensation)		
Continuous operation*3	24 hours		

*1 Approx. 75 % during optical ID transmission. Flickering might occur due to brightness changes during optical ID transmission. *2 Based on IEC 62087 Ed.2 measurement method. *3 Periodical display of moving video is recommended to prevent and/or correct image burn-in where a still image is displayed for long periods.

Optional Accessories

■ Pedestal
TY-ST43PE8

■ Early Warning Software
ET-SWA100 Series*

■ Auto Display Adjustment Upgrade Kit
TY-VUK10 Series

■ Digital Interface Box
ET-YFB100G

■ DIGITAL LINK Switcher
ET-YFB200G

* Part number suffix may differ depending on the license type.

Panasonic®

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Product availability differs depending on region and country. This product may be subject to export control regulations. HDMI, the HDMI logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. The PLink trademark is an application trademark in Japan, the United States, and other countries and regions or registered trademarks. All other trademarks are the property of their respective trademark owners. © 2020 Panasonic Corporation. All rights reserved.



For more information about Panasonic Professional Displays, please visit:
Display Global Website – panasonic.net/cns/prodisplays
YouTube – www.youtube.com/PanasonicProDisplay

All information included here is valid as of April 2020.

SF1HPRE2 Printed in Japan.